

REGD PCT/IR 31 NOV 2003


PCT/IR 3 / 05405
05.01.04



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PCT/IR03/05405




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 19 November 2003

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY



1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

02DEC02 5767560-14 000073
P01/7700 0.00-0227939.6

1. Your reference

6.70.1045 UK

2. Patent application number

(The Patent Office will fill in this part)

0227939.6

29 NOV 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

INTERBREW S.A.
VARSTRAAT 94
B-3000 LEUVEN
BELGIUM

Patents ADP number (if you know it)

906530002

If the applicant is a corporate body, give the country/state of its incorporation

A BELGIAN CORPORATION

4. Title of the invention

VALVE AND SPEAR ASSEMBLY FOR ALCOHOL
BEVERAGE DISPENSING APPARATUS

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

G.F. REDFERN & CO.
LYNN HOUSE
IVY ARCH ROAD
WORTHING
WEST SUSSEX. BN14 8BX

Patents ADP number (if you know it) 8435356 001

1412002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

VALVE AND SPEAR ASSEMBLY FOR ALCOHOL BEVERAGE
DISPENSING APPARATUS

Field of the Invention

The present invention relates to a valve and spear assembly adapted for filling a bag with an alcohol beverage where the bag is contained in a container. In particular, the present invention relates to a valve and spear assembly constructed as a separate component part for use with an alcohol beverage dispensing apparatus.

Background of the Invention

It is known to contain alcohol, such as wine in bags contained in a cardboard type container. Further, it is known to use a bag inserted into a keg for storing beer in the bag. In the case of a beer keg, pressure is applied to the bag to dispense the beer from the bag and out of the keg. Further, the bag is inserted into the keg container prior to the beer being filled into the bag.

The filling of beer into the bag, has two potential problems. One problem is that the bag still may contain air that mixes with the beer and spoils the beer. Another problem is that the filling of the beer directly

into the bag has been known to rupture the bag.

Summary of the Invention

It is an object of the present invention to provide a valve and spear assembly for use with an alcohol beverage or beer dispensing apparatus that reduces the risk of the bag retaining air when filled with beer.

It is another object of the present invention to provide a valve and spear assembly that is a separate component part of the an alcohol dispensing apparatus that may be cleaned and recycled.

It is another object of the present invention to provide a valve assembly and spear assembly for an alcohol beverage or beer dispensing apparatus that is adapted to fill the bag with alcohol, is adapted to supply a pressure in the container against the bag for dispensing the alcohol from the bag, and reduces the chances of the bag rupture during filling of the bag.

The present invention relates to a valve and spear assembly for use with a container housing a bag adapted to be filled with an alcohol beverage. The valve and spear assembly has a valve body having first, second and third spaced apart passageways extending through the valve body. The assembly has first, second and third valves respectively seated in the first second and third passageways to control flow of one of charging gas and beverage through the first and second passageways and to control the flow of pressurizing gas through the third passageway. The assembly has an elongated hollow spear extending from and connected in fluid flow communication with the first passageway for dispensing the beverage from the bag. The hollow spear has an open end portion spaced from the first passageway.

By providing a separate component part comprising the valve and

spear assembly, there is provided a part that may be removed from the container, cleaned and re-used.

Preferably, the first passageway has a tubular extension extending from the valve body that is adapted to extend into the bag, and the hollow spear is secured to the tubular extension.

Preferably, the spear has an outside diameter and the hollow tube extension has an inside diameter corresponding to the outside diameter of the spear whereby the spear is inserted into the hollow tubular extension by interference fit.

In accordance with an aspect of the present invention there is provided a valve and spear assembly for use with a container housing a bag adapted to be filled with an alcohol beverage. The valve and spear assembly comprises a valve body having first, second and third spaced apart passageways extending through the valve body. The assembly has a first valve seated in the first passageway for controlling the flow of one of charging gas and beverage through the first passageway. The assembly has a second valve seated in the second passageway for controlling the flow of one of charging gas and beverage through the first passageway. The assembly has a third valve seated in the third passageway for controlling the flow of pressurizing gas through the third passageway. The assembly has an elongated hollow spear extending from and connected in fluid flow communication with the first passageway. The hollow spear has an open end portion spaced from the first passageway.

Brief Description of The Drawings

For a better understanding of the nature and objects of the present invention reference may be had to the accompanying diagrammatic drawings in which:

Figure 1 is a front elevation view of a home beer dispensing apparatus in accordance with the present invention;

Figure 2 is a side elevation view of the home beer dispensing apparatus;

Figure 3 is broken away perspective view of the keg showing the valve and spear assembly mounted within the keg;

Figure 4 is a sectional side view of the valve and spear assembly as shown in Figure 3;

Figure 5 is a perspective view of the valve and spear assembly outside of the keg;

Figure 6 is a plan view of the valve body of the valve assembly; and,

Figure 7 to 10 are simplified sectional views of the valve body showing valve operation.

Detailed Description Of The Invention

Referring to Figures 1 and 2 there is shown a home beer dispensing apparatus, appliance or unit 10. The dispensing apparatus 10 is primarily intended for use in domestic kitchens but may also be used in utility rooms, garages, domestic bars, caravans etc. While the preferred embodiment relates to dispensing beer, alternatively carbonated solutions or other alcohol beverages may be dispensed by apparatus 10.

The home beer dispensing apparatus 10 has a front wall 12 and a dispensing tap 14 protruding forward of the front wall 12. A drip tray 16 also protrudes forward of the front wall 12 and is adapted to support an open glass container 18 below the dispensing tap 14. The home beer dispensing apparatus 10 further has a base 21 adapted to rest on a counter top. The front wall 12 is an extension of two pivoting side walls 20

which may be moved between closed and open positions to allow the keg 22 (see Figure 2 in broken lines) to be inserted into the housing of the home beer dispensing apparatus 10.

The housing of the home beer dispensing apparatus 10 further includes a top wall 24 and a rear wall 26. The rear wall 26 has a grill 30 that permits for air circulation within the home beer dispensing apparatus 10. An electrical cord 32 extends through the rear wall 26 of the apparatus 10 to provide a connection into a main electrical supply to supply electrical power to the electrical components housed within the unit 10. Alternatively, a 12 Volt DC supply input may be used.

The dispensing apparatus 10 has a cooling system 34 located behind and below keg 22 that is adapted to cool beer in keg 22 when keg 22 is placed into dispensing apparatus 10

Referring now to Figures 3 through 6, the valve assembly 40 and spear 102 are shown.

The valve assembly 40 is adapted to fit into a raised collar aperture 42 of keg 22. The valve assembly 40 has an annular shaped body 46 that is secured in the aperture 42. The valve body 46 has an annular groove 47 and flange 49 that is adapted to extend above the keg 22 for mating with a tap dispensing adapter (not shown) connected to tap 14 (see Figures 1 and 2).

The valve body 46 has a first passageway 48, a second passageway 50, and a third passageway 52 spaced apart from each other and extending through the valve body 46. As best seen in Figure 6, the first passageway 48 is centrally disposed or located within the valve body 46 and the second and third passageways 50, and 52 are spaced radially of the first central passageway 48.

The valve assembly includes a first valve 54, a second valve 56 and a third valve 58. The first valve 54 is seated in the first passageway 48 for controlling the flow of the beverage or beer through the first passageway 48 into and out of the bag 44.

The second valve 56 is seated in the second passageway 50 for controlling the flow of gas such as carbon dioxide through the second passageway 50 into and out of the bag.

The third valve 58 is seated in the third passageway 52 and controls the flow of gas through the third passageway 52 into and out of the keg 22 exterior to the bag 44.

Each valve, 54, 56, and 58 has a valve actuator or stem 60 that effectively opens and closes the valve. The valve stem 60 extends away from the valve body 46 by a different predetermined distance for each of valves 54, 56 and 58. Each of the valves 54, 56 and 58 further includes a valve head 70 connected to the valve stem 68. The valve head 70 carries an O-ring 72 which is adapted to seal the valve head within the respective passageway. A spring 74 urges the valve head 70 into sealing engagement with its corresponding passageway. The valve stems 68 are accessible from outside the keg 22 for moving each valve head 70 into an open and closed position to respectively enable and inhibit fluid flow through passageways 48, 50 and 52.

The valve body 46 has an annular recessed groove 62 recessed in an inner wall 64 of the valve body 46. The inner wall 64 is positioned within the keg 22. The recessed grooves 62 is adapted for receiving the neck 66 of bag 44 in press fit relation therewith. The annular recessed groove 62 has a diameter that surrounds the first and second passageways 48 and 50. The third passageway 52 is located outside of the diameter of

the recessed groove 62 and as a result, the third passageway 52 is located outside of the bag 44.

The keg 22 has a collar flange 82 which defines the raised collar aperture 42, the valve body 46 has an outer peripheral wall 63 with a recessed groove 61 extending around the outer wall 63. An intermediate ring or bung 80 is adapted to seat the valve body 46 within the raised collar aperture 42. The intermediate ring 80 has inner and outer walls 84, 86. The inner wall 84 has flange 88 extending inwardly thereof that is adapted to fit into the recessed groove 61 of the outer wall 63 of the valve body 46. The outer wall 86 of the intermediate ring 80 has a resilient barb 90 and a locking flange 92 spaced from the barb 90 so as to define a outer locating groove 94 into which the collar flange 82 of the keg 22 is held. The barb 90 is adapted to pass through the aperture 42 and spring back into locking engagement with the collar flange 82 so as to lock the valve assembly 40 in place. Special tools are required to remove the valve assembly 40 and the intermediate ring 80 from the collar flange 82 of the keg 22 once the keg 22 is returned to the brewery for refilling.

In order to ensure that the contents of the keg 22 have not been tampered with, the keg 22 has an anti-tamper ring 96 that overlays the intermediate ring 80, a portion of the keg 22 and a portion of the valve body 46. The intermediate ring 80 has an aperture 98 that passes completely through the intermediate ring 80 to provide a vent passageway. The anti-tamper ring 96 has a flange part 100 that is inserted into the vent aperture 98 of the intermediate ring 80. In the event the anti-tamper ring 96 is removed from the keg 22, vent aperture 98 is open and the contents or any pressure within the keg 22 is released. Further, as a pressure relief feature, the anti-tamper ring 96 is designed to

release from aperture 98 when pressure in keg 22 exceeds a predetermined valve to vent pressurized air through aperture 98.

The valve assembly 40 and the spear assembly 102 provide a combination that may be removed for the purposes of recycling of the valve assembly 40 and the spear assembly 102. The bag neck 66 can be removed from the valve assembly 40 so that this valve 40 and spear 102 assembly may be cleaned and reused with a new bag 44 and bag neck 66. The valve and spear assembly is shown as an independent assembly in Figure 5. In order to accommodate the spear 102, the first passageway 48 of the valve body 46 has a tubular extension 104 that extends downwardly or outwardly from the inner wall 64 of the valve body 46. The spear 102 comprises an elongated hollow tube which may have rounded bottom edges or bottom end 108 that extends the spear and the first passageway 48 of the valve body 46 towards the bottom of the keg 22 and the bottom of the bag 44. The hollow spear 22 has an outside diameter that fits inside the diameter of the tubular extension 104 of the first passageway 48 in an interference type of fit whereby the two parts may be secured together. The interference fit may be a tapering effect between the outer wall of the spear 102 and the inner wall of the tubular extension 104. Alternatively, a snap fit may be utilized.

Referring to Figure 7, the valve assembly 40 is shown with each of its first, second and third valves 54, 56 and 58 in a closed position. The valve stems 68 of each valve 54, 56 and 58 extends a different distance upwardly so that it may be activated in a selective manner described in relation to the method of filling the bag 66 with beer or alcohol beverage.

Referring to Figure 8, the valve assembly 40 is shown secured to the keg 22 with the bag 44 illustratively shown in a smaller circle within

the keg 22. Initially, the bag is deflated when the valve assembly 40, spear 102 and bag 44 are inserted into the keg 22. Next, an engagement ring 110 engages the actuator 70 of the first valve 54 and at the same time an engagement ring 112 engages the actuator 70 of the third valve 58. At this stage, carbon dioxide is blown in through the first valve passageway 48 because the first valve 54 is opened by the engagement ring 110. The carbon dioxide inflates the bag 44 such that the bag is inflated to fill the volume of the keg 22. Further, the carbon dioxide mixes with air trapped in bag 10.

As the bag 44 expands within the container 22 air trapped between the bag 44 and the keg 22 exits through the third passageway 52 because the third valve 58 is open.

Referring to Figure 9, the next step is to insert or fill the bag 44 with beer. Preferably, the larger valve or central valve is used. That is the first valve 54 is opened and at the same time the second valve 56 is opened. In this embodiment, the beer will go in through the first passageway 48 and the carbon dioxide will exit through the second passageway 50 removing any air mixed with the carbon dioxide gas.

Referring to Figure 9A, an alternative arrangement is shown where the bag 44 is loaded with beer in an inverted position. In this position, the smaller valve or second valve 56 is used to insert the beer into the container and the first valve 54 is used to permit the carbon dioxide to exit the bag 44.

The next step is the dispensing step which is shown in Figure 10. An adapter or keg adapter 114 is mounted onto the valve assembly 40 to open valves 54 and 58 such that a dispensing tube 118 is connected to the first passageway 48 whereby when dispense tap 14 opens, the beer flows

up through hollow spear 102 and out the first passageway 48 to the tap 14. At the same time, in order to facilitate this flow of beer, the exterior wall of the bag 44 is pressurized. This is done by a pressure system (not shown) which is attached to the third passageway 52 and with the third valve 58 open to permit pressurized air to enter through the third passageway 52.

The different predetermined heights or extensions of the valve actuator 60 of each of the first, second and third valves 54, 56 and 58 permits for different valves to be actuated or opened by the dispenser ring in a selective manner.

WHAT IS CLAIMED IS:

1. A valve and spear assembly for use with a container housing a bag adapted to be filled with an alcohol beverage, the valve and spear assembly comprising:

a valve body having first, second and third spaced apart passageways extending through the valve body;

a first valve seated in the first passageway for controlling the flow of one of charging gas and beverage through the first passageway;

a second valve seated in the second passageway for controlling the flow of one of charging gas and beverage through the first passageway;

a third valve seated in the third passageway that is for controlling the flow of pressurizing gas through the third passageway; and,

an elongated hollow spear extending from and connected in fluid flow communication with the first passageway, the hollow spear having an open end portion spaced from the first passageway.

2. The valve and spear assembly of claim 1 wherein the first passageway has a tubular extension extending from the valve body and adapted to extend into the bag, and wherein the hollow spear is secured to the tubular extension.

3. The valve and spear assembly of claim 2 wherein the hollow spear is secured to the tubular extension by interference fit.

4. The valve and spear assembly of claim 3 wherein the spear has an outside diameter and the hollow tube extension has an inside diameter corresponding to the outside diameter of the spear whereby the spear is inserted into the hollow tubular extension by interference fit.

5. The valve and spear assembly of claim 1 wherein each valve has a valve actuator for opening and closing the valve that extends away

from the valve body and container by a different predetermined distance permitting for selective actuation of the actuators.

6. The valve and spear assembly of claim 1 wherein one of the first, second and third passageways is centrally disposed of the valve body and the other two passageways are spaced radial thereof.

7. The valve and spear assembly of claim 6 wherein the first passageway is the one passageway that is centrally disposed of the valve body.

8. The valve and spear assembly of claim 6 wherein each valve has a valve actuator for opening and closing the valve that extends away from the valve body and container by a different predetermined distance.

9. The valve and spear assembly of claim 8 wherein the first passageway is the one passageway that is centrally disposed of the valve body.

10. The valve and spear assembly of claim 9 wherein the valve body has an annular shape.

11. The valve and spear assembly of claim 10 wherein the valve body has an annular ring adapted to extend above the container for mating with a dispensing adapter.

12. The valve and spear assembly of claim 10 wherein the valve body has an annular recessed groove positioned within the container for receiving a neck of the bag in press fit relation therewith.

13. The valve and spear assembly of claim 11 wherein the annular recessed groove has a diameter that surrounds the first and second passageways.

14. The valve and spear assembly of claim 9 wherein the valve body has a recessed groove positioned within the container for receiving

a neck of the bag in press fit relation therewith.

15. The valve and spear assembly of claim 14 wherein the recessed groove surrounds the first and second passageways.

16. The valve and spear assembly of claim 1 wherein the first, second and third valves each comprise stem valves having a valve piston and a valve head, each said valve stem is accessible from outside the container for moving the valve head into open and closed positions respectively enabling and inhibiting fluid flow through a respective passageway in the valve body.

17. The valve and spear assembly of claim 16 wherein each valve head carries an o-ring for sealing against a surface of the respective passageway in the valve body and a spring seated in the respective passageway for urging the valve head into a closed position.

18. The valve and spear assembly of claim 16 wherein each valve stem extends a different predetermined distance from the valve body to permit for selective actuation of the valves.

VALVE AND SPEAR ASSEMBLY FOR ALCOHOL BEVERAGE
DISPENSING APPARATUS

ABSTRACT

A valve and spear assembly for use with a container housing a bag adapted to be filled with an alcohol beverage has a valve body having first, second and third spaced apart passageways extending through the valve body. The valve assembly has first, second and third valves respectively seated in the first, second and third passageways to control flow of one of charging gas and beverage through the first and second passageways and to control the flow of pressurizing gas through the third passageway. The first passageway has a tubular extension extending from the valve body that is adapted to extend into the bag. The assembly has an elongated hollow spear extending from and connected by interference fit in fluid flow communication with the tubular extension of the first passageway for dispensing the beverage from the bag. The hollow spear has an open end portion spaced from the first passageway. By providing a separate component part comprising the valve and spear assembly, there is provided a part that may be removed from the container, cleaned and re-used.




FIG. 1




FIG. 2.




FIG 3




FIG. 4




FIG. 5




FIG. 6.




FIG. 7




FIG. 8




FIG. 9





FIG. 9a



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.